



PTFE AWG 24-10 (19np) cRUus UL 1659 I A/B 250°C 600V FT1

Construction

- Conductor: nickel plated copper
- Insulation material: Fp-PTFE/a variety of insulation colors available

Technical Data

- Operating voltage (U rms): 600V
- Test voltage (U rms): 6kV
- Resistance at 20°C: max. 34,2 Ω/km
- Temperature range: -190°C to +250°C

Properties

- Cable according to EU-2011/65/EU (RoHS).

AWG	Stranding	Nominal Insulation Thickness in/mm	Nominal Outer Diameter in/mm	Weight Ibs/lkft kg/km	Article-Number
24	19/36	0.020/0.5	0.068/1.7	4/7	55742490+Color
22	19/34	0.020/0.5	0.074/1.9	6/9	55742290+Color
20	19/32	0.020/0.5	0.083/2.1	8/12	55742090+Color
18	19/30	0.020/0.5	0.093/2.4	11/16	55741890+Color
16	19/29	0.020/0.5	0.099/2.5	13/19	55741690+Color
14	19/27	0.020/0.5	0.111/2.8	18/26	55741490+Color
12	19/25	0.020/0.5	0.130/3.3	26/39	55741290+Color
10	37/26	0.020/0.5	0.154/3.9	38/56	55741070+Color

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr