

Silicone UL 3135 Rigid

Construction

- Conductor: rigid
- Core insulation: silicone compound acc. to UL 758
- Marking: printing and label

Technical Data

- Test voltage: 2.000 V
- Operating voltage U₀/U: 600 V
- Temperature: -50°C to +200°C
- minimum bending radius: 5 x d₂
- halogen-free acc. to IEC 60754-1

| AWG- Number | Construction max.mm | Core Ø mm | max. conductor res. Ω/km | Cu- Weight kg/km | Total weight kg/km | Article number |
|----------------|------------------------|--------------|--------------------------------|------------------------|--------------------------|---------------------|
| 22 | 1 x 0,70 | 2,30 | 56,40 | 3,65 | 8,00 | 7802200 + colour |
| 20 | 1 x 0,81 | 2,40 | 35,20 | 4,80 | 10,00 | 7802000 + colour |
| 18 | 1 x 1,13 | 2,70 | 22,20 | 9,60 | 15,00 | 7801800 + colour |
| 16 | 1 x 1,38 | 3,00 | 14,00 | 14,40 | 21,00 | 7801600 + colour |
| 14 | 1 x 1,78 | 3,40 | 8,78 | 24,00 | 31,00 | 7801400 + colour |
| 12 | 1 x 2,26 | 3,90 | 5,53 | 38,40 | 46,00 | 7801200 + colour |

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr