



FEP AWG 26-10 tinned, np, sp AWM/UL 1332

Construction:

- Conductor: tinned copper, nickel-plated copper, silver-plated copper
- Insulation material: Fp-FEP/a variety of insulation colors available

Technical Data

- Operating voltage(U rms): 300 V
- test voltage: 4000 V
- Temperature range: -100°C to 200°C
- Flammability (tested): UL2556 VW-1

Properties

- high electrical, chemical and thermal qualities
- Cable according to EU-2011/65/EU (RoHS).

Produced and printed according to UL 758 AWM Style 1332 E-File 472542

AWG	Stranding	Nominal Insulation Thickness mm	Nominal outer diameter mm	kg/km	Article-number
26	7/34	0,33	1,2	3	57673267+Color
26	19/38	0,33	1,2	3	57673269+Color
24	7/32	0,33	1,3	5	57673247+Color
24	19/36	0,33	1,3	5	57673249+Color
22	7/30	0,33	1,45	6	57673227+Color
22	19/34	0,33	1,45	6	57672229+Color
20	7/28	0,33	1,7	9	57673207+Color
20	19/32	0,33	1,85	9	57673209+Color
18	7/26	0,33	1,9	12	57672187+Color
18	19/30	0,33	2,0	13	57672189+Color
16	7/24	0,33	2,15	16	57672167+Color
16	19/.0117	0,33	2,18	16	57672169+Color
14	7/22	0,33	2,6	25	57672147+Color

AWG	Stranding	Nominal Insulation Thickness mm	Nominal outer diameter mm	kg/km	Article-number
14	19/.0147	0,33	2,9	25	57672149+Color
12	19/.0186	0,33	3,4	39	57672129+Color
10	37/26	0,33	4,4	39	57672109+Color

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr