

Power cord SOOW 600V UL62 and CSA 90°C 4xAWG8+2xAWG16

Construction

- Conductors: Flexible stranded bare copper in acc. with ASTM B3 and UL62
- Seperator: Paper tape over AWG8 cores
- Insulation: EPR compound Class 3 comply with Table 8 of UL 62
- Colour code:
4/C 8AWG: black, white, red, green
2/C 16AWG: black, red
- cabling:
AWG 8 insulated conductors are assembled round together, around central rubber support member
AWG 16 insulated conductors and rubber fillers are placed in interstices
- Seperator: polyester tape
- outer jacket: CPEcompound Class 1.4 comply to tabelle 11 of UL 62
- Colour of outer jacket: black
- Printing according to UL62 E501490

Technical specification

- operating voltage UL: 600 V
- Temperature range: -40°C to +90°C

Applications

- excellent flexibility, resistant to oil, solvents, ozone, sunlight and water
- good weather resistance
- Minimum bending radius: 6 x total diameter of the cable

cores	jacket thickness	overall Ø	weight 305 m	articeln.
4xAWG8+2xAWG16	3,17 mm	24,00 mm	278 kg	2180481621

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr