



PFA/PFA 4xAWG28/7 n.p.c.white PFA 250°C OD=2,30+/-0,15mm

Construction:

- Conductor: n.p.c. (7x0,127mm)
- Conductor diameter: 0,38 mm
- Insulation: PFA
- Insulation diameter: 0,70 +/- 0,05 mm
- Stranding: 4 x Core AWG 28 (2 x wh, 2 x rd)
- Diameter: 1,70 mm
- sheath: PFA white
- Outer diameter: 2,30 +/- 0,15 mm

Technical Data:

- Conductor construction: AWG28 (7x0,127mm)
- Resistance at 20°C: max. 221,78 Ohm/km (AWG28)
- Nominal voltage: 250 V AC
- Test voltage - spark test core: 2,9 kV AC
- Test voltage - spark test sheath: 2,9 kV AC
- Test voltage - core / core: 3,0 kV AC
- Temperature range: min. -190°C / max. +250°C
- Bending radius
 - Fixed installation: 7,5 x D
 - Free movement: 15 x D
- Weight: 9,7 kg/km

Remark: REACH (1907/2006/EG) and RoHS (2015/863/EU) compliant

Articlenumber: 5782504281

-
- Weitere Anfertigungen auf Anfrage
 - Alle Angaben ohne Gewähr