

## H07V2-K according to VDE 0285

### Construction

- Conductor: copper bare according to EN 13602
- Core insulation: PVC high temperature

### Technical Data

- Test voltage: 2.500 V
- Operating voltage U<sub>0</sub>/U: 450/750 V
- Temperature  
range moved -5°C to +90°C  
range static -30°C to +90°C

Ø Size mm <sup>2</sup>	Construction max.mm	Core Ø mm	max. conductor res. Ω/km	Cu- Weight kg/km	Total weight kg/km	Article number
1,50	30 x 0,25	3,25	13,30	14,40	21,50	02300150 + Farbe
2,50	50 x 0,25	3,70	7,98	24,00	32,00	02300250 + Farbe
4,00	56 x 0,30	4,20	4,95	38,00	49,00	02300400 + Farbe
6,00	84 x 0,30	4,80	3,30	58,00	70,00	02300600 + Farbe
10,00	EN 60228; Kl. 5	6,20	1,91	96,00	107,20	02301000 + Farbe
16,00	EN 60228; Kl. 5	7,45	1,21	158,00	170,00	02301600 + Farbe
25,00	EN 60228; Kl. 5	9,30	0,78	240,00	300,00	02302500 + Farbe
35,00	EN 60228; Kl. 5	10,70	0,55	340,00	400,00	02303500 + Farbe

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr