



LiYCY UL 2464/2517-10002 AWG 24

Construction

- Conductor: TPC - tin plated copper acc. EN 13602
- Stranding: AWG 24 - 7 x 0,203 mm
- Core insulation: PVC semi rigid
- Core Diameter: 1,20 mm
- Shielding: Copper braid tinned
- Outer sheath: UL-PVC 105°C
- Marking: printing and label

Technical Data

- Test voltage: 1.500 V
- Operating voltage UL: 300 V
- Conductor resistance: 94,200 Ω /km
- Temperature range moved -10°C to +105°C
- Temperature range static 30°C to +105°C

Properties

- flame retardant acc. to UL 1581 VW-1/ UL2556 FV-2
Style 2464 80°C, Style 2517 105°C

No. of cores	Outer diameter mm	Cu-Weight kg/km	Total weight kg/km	Article number
2	4,60	14,30	28,1	4060240200
3	4,70	16,90	31,4	4060240300
4	5,10	23,40	36,5	4060240400
6	5,70	28,00	39,0	4060240600
8	6,20	31,10	50,0	4060240800
10	7,00	37,10	58,0	4060241000
12	7,10	50,60	64,0	4060241200
14	7,70	55,90	86,0	4060241400
16	8,10	58,80	85,0	4060241600
18	8,50	63,40	112,0	4060241800

No. ofcores	Outer diameter mm	Cu-Weightkg/km	Total weight kg/km	Article number
5	4,90	11,5	33,50	4060240500

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr