



LiYCY UL 2464/2517-10002 AWG 20

Construction

- Conductor: TPC - tin plated copper acc. EN 13602
- Stranding: AWG 20 - 7 x 0,320 mm
- Core insulation: PVC semi rigid
- Core Diameter: 1,50 mm
- Shielding: copper braid tinned
- Outer sheath: UL-PVC 105°C
- Marking: printing and label

Technical Data

- Test voltage: 1.500 V
- Operating voltage UL: 300 V
- Conductor resistance: 37,400 Ω /km
- Temperature range moved -10°C to +105°C
- Temperature range static -30°C to +105°C

Properties

- flame retardant acc. to UL 1581 VW-1/ UL2556 FV-2
Style 2464 80 °C, Style 2517 105 °C

No. of cores	Outer diameter mm	Cu-Weight kg/km	Total weight kg/km	Article number
2	5,20	21,70	41,00	4060200200
3	5,40	27,30	48,00	4060200300
4	5,90	32,90	58,00	4060200400
6	6,80	46,40	78,00	4060200600
8	7,40	66,30	102,00	4060200800
10	8,30	83,00	120,00	4060201000
12	8,40	99,60	133,30	4060201200
14	9,10	100,00	151,70	4060201400
16	9,50	116,50	170,00	4060201600
18	10,00	128,10	195,80	4060201800

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr