

YCY-JZ, transparent - 6,00 mm² - 10,0 mm²

Construction

- Conductor: copper wire bare, stranded
- Construction: acc. to VDE 0295, class 5 or IEC 60228, cl. 5
- Cores: Special PVC
- Marking of Cores: black with ongoing printed numbers
- Protective conductor: green-yellow (from 3-core) in outer layer
- Cores with optimal lay lengths stranded in layers
- Intermediate sheath: out of special PVC
- Shielding: out of tinned copper wires
- Outer sheath: special PVC
- Sheath color: transparent

Technical Datas

- Nom. voltage: 300/500 V
- Test voltage: 4000 V
- Insulation resistance at 20°C: $\geq 20 \text{ MOhm} \times \text{km}$
- Bending radius: 20 x cable diameter
- Temperature range:
 - moved -5°C to +70°C
 - unmoved -30°C to +70°C

Properties

- Flame resistance acc. to IEC 60332-1

Ø mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
4 x 6,0	316,0	16,0	538,0	471 + No. of Cores + Ø
5 x 6,0	430,0	17,2	656,0	471 + No. of Cores + Ø
7 x 6,0	542,0	18,7	870,0	471 + No. of Cores + Ø
4 x 10,0	535,0	19,3	748,0	471 + No. of Cores + Ø
5 x 10,0	649,0	21,5	915,0	471 + No. of Cores + Ø

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr