

SY-JZ, transparent - 2,50 mm² up to 6,00 mm²

Construction

- Conductor: copper wire bare, stranded
- Construction: acc. to VDE 0295, class 5 or IEC 60228, cl. 5
- Cores: special PVC
- Marking of Cores: black with ongoing printed numbers
- Protective conductor: green-yellow (from 3-core) in outer layer
- partly from 25,0 mm² - coloured cores acc. to VDE 0293
- Cores with optimal lay lengths stranded in layers
- Intermediate sheath: out of special PVC
- Steel wire braid, galvanized
- Outer sheath: special PVC
- Sheath color: transparent

Technical Datas

- Nom. voltage: 300/500 V
- Test voltage: 2.000 V
- Insulation resistance at +20°C: ≥ 20 MΩm x km
- Bending radius: 20 x cable diameter
- Temperature range
moved -5°C to +70°C
unmoved -30°C to +70°C

Properties

- Flame resistance acc. to IEC 60332-1

Ø mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
3 x 2,50	72,0	12,2	280,0	2780030250
4 x 2,50	96,0	13,7	330,0	2780040250
7 x 2,50	168,0	15,8	420,0	2780070250
4 x 4,0	153,6	16,8	430,0	2780040400
4 x 6,0	230,4	18,2	520,0	2780040600

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr