

Y/EB-JZ - 1,50 mm²

Construction

- Conductor: copper wire bare, stranded
- Construction: acc. to VDE 0295, class 5 or IEC 60228 cl. 5
- Cores: special-PVC
- Marking of cores: black cores with ongoing printed numbers
- Protective conductor: green-yellow (from 3-core) in the outer layer
- Cores with optimal lay lengths: stranded in lays
- Outer sheath: special-PVC
- Sheath color: blue, RAL 5015

Technical Data

- Nom. voltage: 300/500 V
- Test voltage: 2.000 V
- Insulation resistance at 20°C: $\geq 20 \text{ M}\Omega \times \text{km}$
- Bending radius: 15 x cable diameter
- Temperature range
moved -5°C to +70°C
unmoved -30°C to +70°C

Properties

- Flame resistance acc. to IEC 60332-1

Ø mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
2 x 1,5 OZ	28,8	6,6	100,0	2680020150
3 x 1,5	43,2	6,8	110,0	2680030150
4 x 1,5	57,6	7,4	125,0	2680040150
5 x 1,5	72,0	8,3	145,0	2680050150
7 x 1,5	100,8	9,1	195,0	2680070150

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr