

## YCY-JZ (OZ) 0,6/1, black - from 25,0 mm<sup>2</sup>

Flexible, UV-resistant control cable with overall copper braided screening; preferred EMC compatible cable type

### Construction

- Conductor: stranded bare Cu conductor, fine wire
- Construction: strand structure to VDE 0295, class 5 / IEC 60228 class 5
- Core insulation: special PVC
- Black cores with printed consecutive white number coding
- Protective conductor:  
JZ = green-yellow protective conductor in the outer layer (3 cores and over)  
OZ = without protective conductor
- Cores twisted in layers, with optimal lay lengths
- Special PVC inner jacket, black
- Braided Screening made of tinned copper wires
- Outer sheath: special PVC, flame retardant and UV-resistant
- Sheath color: black, RAL 9005

### Technical Data

- Rated voltage: U<sub>0</sub>/U 600/1000 V
- Test voltage: 4.000 V
- Insulation resistance: ≥ 20 MΩhm x km
- Bending radius: 20 x cable diameter
- Temperature range:  
flexible -5°C to +70°C  
stationary -30°C to +70°C

### Properties

- Flame retardant acc. to IEC 60332-1

Ø mm <sup>2</sup>	Cu-Weight kg/km	Outer diameter mm	Total-Weight kg/km	Article number
4 x 25,0	1.165,0	29,8	2.179,0	472 + no. of cores + diameter
5 x 25,0	1.400,0	31,6	2.590,0	472 + no. of cores + diameter
4 x 35,0	1.638,0	32,7	2.893,0	472 + no. of cores + diameter
4 x 50,0	2.368,0	39,6	4.094,0	472 + no. of cores + diameter
4 x 150,0	6.538,0	67,9	8.095,0	472 + no. of cores + diameter

Ø mm²	Cu-Weightkg/km	Outer diametermm	Total-Weight kg/km	Article number
4 x 185,0	7.760,0	74,0	9.576,0	472 + no. of cores + diameter

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr