



Multiflex® LiCP - 0,25 mm²

Highly flexible screened electronics cable for use on drag chains; preferred EMC compatible cable type

Construction

- Conductor: stranded bare Cu conductor, extra-fine wire
- Strand structure to VDE 0295, class 6 / IEC 60228 class 6
- TPE-insulated cores
- Core identification to DIN 47100
- Cores twisted in layers, with optimal lay lengths
- Fabric lapping
- Braided screening made of tinned copper wires
- Fabric lapping
- Outer sheath: special PUR, cold flexible, halogen-free, oil-resistant
- Sheath colour: RAL 7001 grey

Technical Data

- Peak operating voltage: 0.14 mm² 350 V
> 0.14 mm² 500 V
(not approved for use as mains power cable!)
- Test voltage: 1.500 V
- Insulation resistance at +20°C: ≥ 20 Mohm x km
- Bending radius: 12 x cable diameter
- Temperature range:
flexible -40°C to +80°C
stationary -50°C to +80°C

Properties

- Oil-resistant to DIN EN / IEC 60811-2-1

Ø mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
2 x 0,25	18,1	5,7	35,0	2940200250
3 x 0,25	20,7	5,9	40,0	2940300250
4 x 0,25	25,3	6,1	46,0	2940400250
5 x 0,25	28,1	6,6	53,0	2940500250
7 x 0,25	45,8	7,4	74,0	2940700250
12 x 0,25	66,9	8,9	107,0	2941200250
18 x 0,25	84,9	10,3	139,0	2941800250

Ø mm²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
24 x 0,25	113,5	12,3	188,0	2942400250

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr