

HSLH-JZ - 10,00 mm²

Halogen-free machine control cable with enhanced fire protection properties

Construction

- Conductor: stranded bare Cu conductor, fine wire
- Strand structure to VDE 0295 class 5 / IEC 60228 class 5
- Core insulation: halogen-free compound
- Black cores with printed consecutive number coding
- Green-yellow protective conductor (3 cores and over) in the outer layer
- Cross-sections 35.0 mm² and over with cores coloured to VDE 0293
- Special versions without protective conductor "OZ"
- Cores twisted in layers, with optimal lay lengths
- Outer sheath: halogen-free compound
- Sheath colour: RAL 7001 grey

Technical Data

- Rated voltage: Uo/U 300/500 V
- Test voltage: 4000 V
- Bending radius: 15 x cable diameter
- Temperature range:
 - flexible -15°C to +70°C
 - stationary -40°C to +70°C

Properties

- Flame retardant to IEC 60332-3
- Halogen-free to IEC 60754-1 and IEC 60754-2

Special characteristics

- reduced fire propagation
- low smoke emission
- low fire load
- no corrosiveness
- recyclable

Ø mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
4 x 10,0	384,0	16,7	750,0	2604100000
5 x 10,0	480,0	18,1	930,0	2605100000
7 x 10,0	672,0	20,0	1.105,0	2607100000

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr