

HSLCH-JZ - 16,00 mm²

Halogen-free machine control cable with overall copper braided screening; preferred EMC compatible cable type

Construction

- Conductor: stranded bare Cu conductor, fine wire
- Strand structure to VDE 0295 class 5 / IEC 60228 class 5
- Core insulation: halogen-free compound
- Black cores with printed consecutive number coding
- Green-yellow protective conductor (3 cores and over) in the outer layer
- Special versions without protective conductor: "OZ"
- Cross-sections 35.0 mm² and over with cores coloured to VDE 0293
- Cores twisted in layers, with optimal lay lengths
- Lapped with plastic film
- Braided screening made of tinned copper wire
- Outer sheath: halogen-free compound
- Sheath colour: RAL 7001 grey

Technical Data

- Rated voltage: U₀/U 300/500 V
- Test voltage: 4000 V
- Bending radius: 15 x cable diameter
- Temperature range:
 - flexible -15°C to +70°C
 - stationary -40°C to +70°C

Properties

- Flame retardant to IEC 60332-3
- Halogen-free to IEC 60754-1 and IEC 60754-2

Special characteristics

- reduced fire propagation
- low smoke emission
- low fire load
- no corrosiveness
- recyclable

Ø mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
2 x 16,0 OZ	420,0	17,0	570,0	2502160020
3 x 16,0	750,0	18,4	890,0	2503160000
4 x 16,0	810,2	20,2	1.030,0	2504160000
5 x 16,0	1.050,0	22,2	1.120,0	2505160000
7 x 16,0	1.470,0	24,8	1.482,0	2507160000

- Weitere Anfertigungen auf Anfrage

- Alle Angaben ohne Gewähr