

## SiHF-J - 2,50 mm<sup>2</sup>

Highly heat-resistant, silicone-sheated flexible cable

### Construction

- Conductor: stranded tinned Cu conductor, fine wire
- Strand structure to VDE 0295 class 5 / IEC 60228 class 5
- Silicone-insulated cores
- Up to 5 cores: coloured cores to VDE 0293
- 6 cores and over: black cores with printed consecutive number coding
- Green-yellow protective conductor (3 cores and over) in the outer layer
- Cores twisted in layers, with optimal lay lengths
- Outer sheath: silicone
- Sheath colour: preferably reddish brown

### Technical Data

- Rated voltage: U<sub>0</sub>/U 300/500 V
- Test voltage: 2.000 V
- Insulation resistance: ≥ 200 MΩm x km
- Bending radius: 15 x cable diameter
- Temperature range: -50°C to +180°C  
temporarily up to +200°C

### Properties

- Flame retardant to IEC 60332-1
- Halogen-free: HCl emission to IEC 60754-1
- Corrosiveness of combustion gas to IEC 60754-2

Ø Size mm <sup>2</sup>	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
2 x 2,50	48,0	9,2	135,0	8200202500
3 x 2,50	72,0	9,7	152,0	8200302500
4 x 2,50	96,0	10,6	189,0	8200402500
5 x 2,50	120,0	11,6	229,0	8200502500
6 x 2,50	144,0	12,6	268,0	8200602500
7 x 2,50	168,0	12,6	293,0	8200702500
12 x 2,50	288,0	18,0	580,0	8201202500
24 x 2,50	576,0	23,0	850,0	8202402500

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr