

SiHF/GL/P-J - 6,00 to 16,00 mm²

Highly heat-resistant, silicone-sheathed flexible cable with glass fibre and armoured braid

Construction

- Conductor: stranded tinned Cu conductor, fine wire
- Strand structure to VDE 0295 class 5 / IEC 60228 class 5
- Silicone-insulated cores
- Up to 5 cores: coloured cores to VDE 0293
- 6 cores and over: black cores with printed consecutive number coding
- Green-yellow protective conductor (3 cores and over) in the outer layer
- Cores twisted in layers, with optimal lay lengths
- Outer sheath: silicone
- Sheath colour: preferably reddish Brown
- Glass fibre braiding
- Armoured braid made of galvanized steel wire

Technical Data

- Rated voltage: U₀/U 300/500 V
- Test voltage: 2.000 V
- Insulation resistance: ≥ 200 MΩm x km
- Bending radius: 20 x cable diameter
- Temperature range: -50°C to +180°C
temporarily up to +200°C

Properties

- Flame retardant to IEC 60332-1
- Halogen-free: HCl emission to IEC 60754-1
- Corrosiveness of combustion gas to IEC 60754-2

Ø Size mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
2 x 6,00	115,2	14,9	346,0	8220020600
3 x 6,00	173,0	15,7	431,0	8220030600
4 x 6,00	230,4	17,7	543,0	8220040600
5 x 6,00	288,0	19,2	655,0	8220050600
4 x 10,00	384,0	21,5	925,0	8220041000
4 x 16,00	614,4	25,8	1.235,0	8220041600

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr