

FLYK

- Conductor: soft annealed electrolyte copper, bare
- Insulation: PVC, cold resistant DIN-ISO 6722, class A
but cold bending test -40°C
- Temperature range: -40°C to + 90°C
- Temperature resistance: valid for the duration of 3.000 h

nom. Ø mm ²	Construction max .mm	Single cores		Resistance at 20 °C max. m ² /m	Insulation wall resistance mm	Outer-Ø min./max. mm/mm	Cu- Weight kg/km	Total weight kg/km	Article number
		Ø max. mm	Ø max. mm						
0,50	16	0,21	1,1	37,1	0,6	2,0/2,3	4,8	8,0	3230500 + colour
0,75	24	0,21	1,3	24,7	0,6	2,2/2,5	7,2	11,0	3230750 + colour
1,0	32	0,21	1,5	18,5	0,6	2,4/2,7	9,6	14,0	3231000 + colour
1,5	30	0,26	1,8	12,7	0,6	2,7/3,0	14,4	19,0	3231500 + colour
2,5	50	0,26	2,2	7,60	0,7	3,3/3,6	24,0	30,0	3232500 + colour
4,0	56	0,31	2,8	4,71	0,8	4,0/4,4	38,0	47,5	3234000 + colour
6,0	84	0,31	3,4	3,14	0,8	4,6/5,0	58,0	68,0	3236000 + colour

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr