



LiYY UL/cUL 2464/2517-10002 AWG 26

Control cable unscreened

Construction

- Conductor: TPC - tin plated copper acc. EN 13602
- Stranding: AWG 26 - 7 x 0,160 mm
- Core insulation: UL-PVC semi rigid
- Core diameter: 1,00 mm
- Outer sheath: UL-PVC 105°C
- Marking: printing and label

Technical Data

- Test voltage: 1.500 V
- Operating voltage UL: 300 V
- Conductor resistance: 150,000 Ω /km
- Temperature
range moved -10°C to +105°C
range static -30°C to +105°C

Properties

- flame retardant acc. to UL 1581 VW-1/ UL2556 FV-2
Style 2464 80°C, Style 2517 105°C

No. of cores	Outer diameter mm	Cu-weight kg/km	Total weight kg/km	Article number
2	3,7	2,8	12,5	4040260200
3	3,8	4,2	15,0	4040260300
4	4,1	5,6	17,5	4040260400
6	4,7	8,4	24,5	4040260600
8	5,1	11,2	34,0	4040260800
10	5,7	14,0	38,0	4040261000
12	5,9	17,0	45,5	4040261200
14	6,2	22,4	52,1	4040261400
16	6,5	22,4	58,2	4040261600
18	6,8	24,6	57,0	4040261800

- Further formats available on request
- All data and products subject to change