

Silicone UL 3239 AWG 14 150°C

Construction / Technical Data / Properties

- Conductor: tinned copper
- Outer diameter conductor: AWG 14
- Core insulation: silicone rubber
- Printing: acc. to UL-standard
- Colour: white, black and red are available
other colors on request
- temperature range: -40°C to +150°C
- flame retardant acc UL VW-1

small amounts (30,5m, 152m, 305m) are available at short notice

stocknumber: 778XX+colour

Ø Core mm ²	wire strength qmm	construction mm	curent voltage	Wall thickness mm	diameter mm	stocknumber
AWG 14	2,08	41 x 0,25	50 kV	3,81	9,50	778350+colour
AWG 14	2,08	41 x 0,25	40 kV	2,46	6,81	778340+colour
AWG 14	2,08	41 x 0,25	30 kV	1,90	5,69	778330+colour
AWG 14	2,08	41 x 0,25	25 kV	1,57	5,03	778325+colour
AWG 14	2,08	41 x 0,25	20 kV	1,27	4,42	778320+colour
AWG 14	2,08	41 x 0,25	15 kV	1,14	4,17	778315+colour
AWG 14	2,08	41 x 0,25	10 kV	1,02	3,91	778310+colour

- Further formats available on request
- All data and products subject to change