



## Silicone UL 3239 AWG 2 -8 150°C

### Construction / Technical Data / Properties

- Conductor: tinned copper
- Outer diameter conductor: AWG 2 - 8
- Core insulation: silicone rubber
- Printing: acc. to UL-standard
- Colour: white, black and red are available  
other colors on request
- temperature range: -40°C to +150°C
- flame retardant acc UL VW-1

small amounts (30,5m, 152m, 305m) are available at short notice

stocknumber: 778XX+colour

| Ø<br>Core<br>mm <sup>2</sup> | wire<br>strength<br>qmm | construction<br>mm | curent<br>voltage | Wall<br>thickness<br>mm | diameter<br>mm | stocknumber   |
|------------------------------|-------------------------|--------------------|-------------------|-------------------------|----------------|---------------|
| AWG 2                        | 34,45                   | 259 x 0,40         | 25 kV             | 1,57                    | 11,76          | 778325+colour |
| AWG 4                        | 21,55                   | 133 x 0,45         | 25 kV             | 1,57                    | 9,98           | 778325+colour |
| AWG 6                        | 13,57                   | 133 x 0,36         | 15 kV             | 1,14                    | 7,70           | 778315+colour |
| AWG 6                        | 13,57                   | 133 x 0,36         | 25 kV             | 1,57                    | 8,56           | 778325+colour |
| AWG 8                        | 8,61                    | 133 x 0,28         | 15 kV             | 1,14                    | 6,58           | 778315+colour |
| AWG 8                        | 8,61                    | 133 x 0,28         | 25 kV             | 1,57                    | 7,44           | 778325+colour |
| AWG 8                        | 8,61                    | 133 x 0,28         | 40 kV             | 2,46                    | 9,22           | 778340+colour |

- Further formats available on request
- All data and products subject to change