



FLRYY 2x0,50-B + 2x1,50-B T105 ADR

Conductor

Material:	E-Copper bare
Construction	0,50-B mm ² 16 x 0,21 mm max. 1,50-B mm ² 30 x 0,26 mm max.
Conductor Diameter	0,50-B mm ² 1,10 mm max. 1,50-B mm ² 1,70 mm max.
Resistance	0,50-B mm ² 37,1 mW/m max. 1,50-B mm ² 12,7 mW/m max.

Insulation Core

Material:	PVC heat resistance T 105
Thickness	FLRY 0,50-B mm ² 0,22 mm min. FLRY 1,50-B mm ² 0,24 mm min
Outer diameter:	FLRY 0,50-B mm ² 1,60 mm max. FLRY 1,50-B mm ² 2,40 mm max.
Shore hardness A	nom. 98 / 96

Stranding

Length of lay / Direction of lay of strand	nom. 144 mm / links
--	---------------------

Insulation Jacket

Material:	PVC heat resistance T 105
Thickness:	1,0 mm min.
Outer diameter:	7,10 ± 0,2 mm
Shore hardness A:	nom. 88

Requirements & Examinations

Temperature range	-40 °C to +105 °C
-------------------	-------------------

Other properties

Cable weight:	ca. 87 g/m
Artikelnummer:	3109925215

-
- Further formats available on request
 - All data and products subject to change