



## Silicone UL 3529 200°C V-FT2

### Construction

- Conductor: flexible tin plated copper
- Insulation: Silicone Rubber according to UL 758
- Marking: CSA AWM I A/B 200°C 600 V FT2 AWM STYLE 3529 E 472542

### Technical Data

- Voltage rating: 600 V
- Temperature rating: +200°C
- Talcum: yes

| AWG-Nr. | Construction mm | Insulation thickness mm | Total Ø mm    | Articlenumber |
|---------|-----------------|-------------------------|---------------|---------------|
| 12      | 51 x 0,30       | 0,76                    | 4,00 +/- 0,2  | U352901210    |
| 14      | 44 x 0,25       | 0,76                    | 3,50 +/- 0,2  | U352901410    |
| 16      | 42 x 0,20       | 0,76                    | 3,20 +/- 0,2  | U352901610    |
| 18      | 26 x 0,20       | 0,76                    | 2,80 +/- 0,10 | U352901810    |
| 20      | 17 x 0,20       | 0,76                    | 2,60 +/- 0,10 | U352902010    |
| 22      | 12 x 0,20       | 0,76                    | 2,40 +/- 0,10 | U352902210    |
| 24      | 7 x 0,20        | 0,76                    | 2,30 +/- 0,10 | U352902410    |

- Further formats available on request
- All data and products subject to change