



Glass silk insulated pure nickel strand 400V, 1,50-10,0mm², + 400°C

Construction:

- Conductor: Pure nickel
- Construction: fine-stranded (see table)
- Insulation: covered with glass silk + impregnated glass silk braid
- Colour: white (natural), green/yellow (other colors on request)

Technical Data:

- Rated voltage: 400 V
- Test voltage: 2000 V
- Minimum bending radius fixed: approx. 18 x cable diameter
- Temperature range: -50°C to +400°C

Dimension	Construction	Outside-Ø in mm	Article-Nr.
1 x 1,50	30 x 0,25	2,90	8101015 white
1 x 2,50	49 x 0,25	3,60	8101025 white
1 x 4,00	84 x 0,25	4,40	8101040 white
1 x 6,00	126 x 0,25	5,00	8101060 white
1 x 10,00	203 x 0,25	6,20	8101100 white
1 x 1,50	30 x 2,50	2,90	8101015 green/yellow
1 x 2,50	49 x 0,25	3,60	8101025 green/yellow
1 x 4,00	84 x 0,25	4,40	8101040 green/yellow
1 x 6,00	126 x 0,25	5,00	8101060 green/yellow
1 x 10,0	203 x 0,25	6,20	8101100 green/yellow

- Further formats available on request
- All data and products subject to change