



## Silicone UL 3604 200°C AWG 1-8

### Construction

- Conductor: Flexible tinned copper
- Insulation: Silicone rubber according to UL 758
- Marking: AWM STYLE 3604 200°C 600V E 472542

### Technical Data

- Voltage rating: 600 V
- Temperature Rating: -60°C to +200°C
- Max temp. of short circuit: 350°C on the conductor
- Use Internal Wiring of Appliances where totally enclosed

| AWG-Nr. | Construction mm | Insulated thickness mm | Total Ø mm        | Max. resistance at 20°C | Articlenumber |
|---------|-----------------|------------------------|-------------------|-------------------------|---------------|
| 1       | 14 x 26         | 2,032                  | 13,60<br>+/- 0,30 | 0,393                   | U360400110    |
| 2       | 10 x 26         | 1,524                  | 11,20<br>+/- 0,30 | 0,565                   | U360400210    |
| 4       | 7 x 26          | 1,524                  | 9,90 +/-<br>0,20  | 0,795                   | U360400410    |
| 6       | 7 x 17          | 1,524                  | 8,70 +/-<br>0,20  | 1,24                    | U360400610    |
| 8       | 7 x 11          | 1,143                  | 6,90 +/-<br>0,20  | 1,95                    | U360400810    |

- Further formats available on request
- All data and products subject to change