



LiYCY UL 2464/2517-10002 AWG 22

Construction

- Conductor: TPC - tin plated copper acc. EN 13602
- Stranding: AWG 22 - 7 x 0,254 mm
- Core insulation: PVC semi rigid
- Core Diameter: 1,30 mm
- Shielding: copper braid tinned
- Outer sheath: UL-PVC 105°C
- Marking: printing and label

Technical Data

- Test voltage: 1.500 V
- Operating voltage UL: 300 V
- Conductor resistance: 59,400 Ω /km
- Temperature range moved -10°C to +105°C
- Temperature range static -30°C to +105°C

Properties

- flame retardant acc. to UL 1581 VW-1/ UL2556 FV-2
Style 2464 80 °C, Style 2517 105 °C

No. of cores	Outer diameter mm	Cu-Weight kg/km	Total weight kg/km	Article number
2	4,80	20,00	32,00	4060220200
3	4,90	24,10	36,00	4060220300
4	5,30	25,00	45,00	4030220400
6	6,20	43,60	61,00	4060220600
8	6,70	49,90	73,00	4060220800
10	7,50	51,40	93,00	4060221000
12	7,80	53,60	102,00	4060221200
14	8,00	71,50	115,50	4060221400
16	8,60	82,80	130,90	4060221600
18	8,70	131,10	195,80	4060220800

- Further formats available on request
- All data and products subject to change