



LiYCY UL 2464/2517-10002 AWG 28

Construction

- Conductor: TPC - tin plated copper acc. EN 13602
- Stranding: AWG 28 - 7 x 0,127 mm
- Core insulation: PVC semi rigid
- Core Diameter: 0,90 mm
- Shielding: copper braid tinned
- Outer sheath: UL-PVC 105°C
- Marking: printing and label

Technical Data

- Test voltage: 1.500 V
- Operating voltage UL: 300 V
- Conductor resistance: 239,000 Ω /km
- Temperature range moved -10°C to +105°C
- Temperature range static -30°C to +105°C

Properties

- flame retardant acc. to UL 1581 VW-1/ UL2556 FV-2
Style 2464 80 °C, Style 2517 105 °C

No. of cores	Outer diameter mm	Cu-Weight kg/km	Total weight kg/km	Article number
2	4,00	10,60	26,00	4060280200
3	4,10	9,50	23,70	4060280300
4	4,30	13,60	27,10	4060280400
6	4,85	14,00	33,90	4060280600
8	5,10	17,60	38,40	4060280800
10	5,80	21,40	48,90	4060281000
12	6,00	24,90	54,10	4030281200
14	6,20	27,80	62,40	4060281400
16	6,50	30,30	63,50	4060281600
18	6,80	32,10	68,60	4060281800

- Further formats available on request
- All data and products subject to change