



H05RR-F acc. to VDE 0285

Construction

- Conductor: copper bare according to EN 13602
- Core insulation: ethylen-propylen-rubber 3G
- Color code: colour code VDE 0293 HD 308 with gn-ye (JB)
- Wall thickness: nom. 0,60 mm
- Outer sheath: EM2 acc. to EN 50363
- Sheat Color: RAL 9005 black

Technical Data

- Test voltage: 2.000 V
- Operating voltage Uo/U: 300/500 V
- Temperature: range static -25°C to +60°C

No. of cores	Size mm ²	Outer diameter mm	Cu-Weight kg/km	Total weight kg/km	Article number
2	0,75	6,55	14,4	60,0	2820200075
3	0,75	7,05	21,6	68,0	2820300075
4	0,75	7,80	29,0	78,0	2820400075
2	1,00	7,05	19,0	72,0	2820200100
3	1,00	7,50	29,0	85,0	2820300100
4	1,00	8,20	38,0	98,0	2820400100
2	1,50	8,70	29,0	98,0	2820200150
3	1,50	9,20	43,0	120,0	2820300150
4	1,50	10,30	58,0	150,0	2820400150
5	1,50	11,25	72,0	180,0	2820500150
2	2,50	10,30	48,0	160,0	2820200250
3	2,50	11,00	72,0	190,0	2820200250
4	2,50	12,20	96,0	238,0	2820400250
5	2,50	13,70	120,0	285,0	2820500250

- Further formats available on request

- All data and products subject to change