

Y-JB 10,00 mm²

Construction

- Conductor: copper wire bare, stranded
- Construction: acc. to VDE 0295, class 5 or IEC 60228, cl. 5
- Cores: Special PVC
- Marking of Cores: colored cores acc. to VDE 093-308
- Protective conductor: green-yellow (from 3-core) in outer layer
- Cores with optimal lay lengths stranded in layers
- Outer sheath: Special PVC
- Sheath color: gray, RAL 7001

Technical Data

- Nom. voltage: 300/500 V
- Test voltage: 4.000 V
- Insulation resistance at 20°C: $\geq 20 \text{ MOhm} \times \text{km}$
- Bending radius: 15 x cable diameter
- Temperature range:
 - moved -5°C to +70°C
 - unmoved -30°C to +70°C

Properties

- Flame resistance acc. to IEC 60332-1

Ø mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
3 y 10,0	288,0	14,9	520,0	2730310000
4 x 10,0	384,0	16,5	660,0	2730410000
5 x 10,0	480,0	18,3	800,0	2730510000
7 x 10,0	672,0	20,2	1.050,0	2730710000

- Further formats available on request
- All data and products subject to change