



Y11Y-JZ - 0,75 mm²

UV-resistant, flexible control cable with PUR outer sheath

Construction

- Conductor: stranded bare Cu, fine wire
- Strand structure to VDE 0295 class 5 / IEC 60228 class 5
- Core insulation: special PVC
- Black cores with White printed consecutive number coding
- Green-yellow protective conductor (3 cores and over) in the outer layer
- Cores twisted in layers, with optimal lay lengths
- Outer sheath: PUR, oil resistant, UV-resistant
- Sheath colour: RAL 7001, grey

Technical Data

- Rated voltage: U₀/U 300/500 V
- Test voltage: 3000 V
- Insulation resistance at +20°C: ≥ 20 MΩ x km
- Bending radius:
 - flexible 15 x cable diameter
 - stationary 6 x cable diameter
- Temperature range:
 - moved -5°C to +70°C
 - unmoved -40°C to +80°C

Properties

- Flame retardant to IEC 60332-1

Special characteristics

- exceptional resistance to mechanical impact
- high abrasion resistance
- high Impact strength
- chemically resistant
- oil-resistant
- UV-resistant

Ø mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
2 x 0,75 0Z	14,4	5,4	43,0	4660200750
3 x 0,75	22,0	5,7	61,0	4660300750
4 x 0,75	28,8	6,2	75,0	4660400750
5 x 0,75	36,0	6,7	100,0	4660500750
7 x 0,75	50,0	7,3	125,0	4660700750
10 x 0,75	72,0	9,6	172,0	4660700750

Ø mm²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
12 x 0,75	86,0	9,9	210,0	4661200750
18 x 0,75	130,0	11,7	270,0	4661800750
25 x 0,75	180,0	14,2	370,0	4662500750

- Further formats available on request
- All data and products subject to change