

SiHF-J - 0,75 mm²

Highly heat-resistant, silicone-sheated flexible cable

Construction

- Conductor: stranded tinned Cu conductor, fine wire
- Strand structure to VDE 0295 class 5 / IEC 60228 class 5
- Silicone-insulated cores
- Up to 5 cores: coloured cores to VDE 0293
- 6 cores and over: black cores with printed consecutive number coding
- Green-yellow protective conductor (3 cores and over) in the outer layer
- Cores twisted in layers, with optimal lay lengths
- Outer sheath: silicone
- Sheath colour: preferably reddish brown

Technical Data

- Rated voltage: U₀/U 300/500 V
- Test voltage: 2.000 V
- Insulation resistance: ≥ 200 MΩm x km
- Bending radius: 15 x cable diameter
- Temperature range: -50°C to +180°C
temporarily up to +200°C

Properties

- Flame retardant to IEC 60332-1
- Halogen-free: HCI emission to IEC 60754-1
- Corrosiveness of combustion gas to IEC 60754-2

Ø Size mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
2 x 0,75	14,4	6,4	53,0	8200200750
3 x 0,75	22,0	6,8	64,0	8200300750
4 x 0,75	28,8	7,8	84,0	8200400750
5 x 0,75	36,0	8,5	101,0	8200500750
6 x 0,75	43,2	9,2	117,0	8200600750
7 x 0,75	50,0	9,2	125,0	8200700750
12 x 0,75	86,0	10,6	170,0	8201200750

- Further formats available on request
- All data and products subject to change