

FLRY-B

- Conductor: soft annealed electrolyte copper, bare
- Insulation: PVC DIN 72551, part 6, type B
- Temperature range: -40°C to + 105°C
- Temperature resistance: valid for the duration of 3.000 h

nom. Ø mm²	Construction max .mm	Single cores Ø max. mm	Ø max. mm	Resistance at 20 °C max. m²/m	Insulation wall resistance mm	Outer-Ø min./max. mm/mm	Cu- Weight kg/km	Article number
0,35	12	0,21	0,9	52,0	0,25	1,2/1,4	3,2	32103512 + Farbe
0,50	16	0,21	1,0	37,1	0,3	1,4/1,6	4,8	32105016 + Farbe
0,75	24	0,21	1,2	24,7	0,3	1,7/1,9	7,2	32107524 + Farbe
1,0	32	0,21	1,35	18,5	0,3	1,9/2,1	9,6	32110032 + Farbe
1,5	30	0,26	1,7	12,7	0,3	2,2/2,4	14,4	32115030 + Farbe
2,5	50	0,26	2,2	7,6	0,35	2,7/3,0	24,0	32125050 + Farbe
4,0	56	0,31	2,75	4,7	0,4	3,4/3,7	38,0	32140056 + Farbe
6,0	84	0,31	3,3	3,1	0,4	4,0/4,3	58,0	32160084 + Farbe

- Further formats available on request
- All data and products subject to change