

Y-JZ/-OZ/-JB 1,5 mm²

- Conductor: bare copper-strand, fine-strand
- Construction: acc. to VDE 0295 class 5 respectively IEC 60228 cl. 5
- Cores: Special-PVC
- Marking Y-JZ/-OZ: black cores with consecutively numerical inscription with protective conductor
green-yellow (from 3-core) in the outer layer
- Marking Y-JB: Coloured cores acc. to VDE 0293-308 with protective conductor
green-yellow (from 3-core) in the outer layer
- OZ = without protective conductor
- Cores: with optimum lengths of lay stranded in layers
- Outer sheath: Special-PVC
- Sheath colour: grey RAL 7001
- Nominal voltage U₀/U: 300 / 500 V
- Test voltage: 4.000 V
- Insulation resistance: at +20°C ≥ 20 MΩm x km
- Bending radius: 15 x cable diameter
- Temperature range:
stationary -30°C to +70°C
moved -5°C to +70°C
- Non-Inflammability: acc. to IEC 60332-1

Ø mm ²	Co-Weight kg/km	Outer-Ø mm	Total weight kg/km	Stock-number
2 x 1,5 OZ	28,8	6,6	100,0	27+no of cores+cross section
3 x 1,5	43,2	6,8	110,0	27+no of cores+cross section
3 x 1,5 OZ	43,2	6,8	110,0	27+no of cores+cross section
4 x 1,5	57,6	7,4	125,0	27+no of cores+cross section
4 x 1,5 OZ	57,6	7,4	125,0	27+no of cores+cross section
5 x 1,5	72,0	8,3	145,0	27+no of cores+cross section
5 x 1,5 OZ	72,0	8,3	145,0	27+no of cores+cross section

Ø mm²	Co-Weightkg/km	Outer-Ø mm	Total weight kg/km	Stock-number
6 x 1,5	86,4	9,0	170,0	27+no of cores+cross section
7 x 1,5	100,8	9,1	195,0	27+no of cores+cross section
7 x 1,5 0Z	100,8	9,1	195,0	27+no of cores+cross section
10 x 1,5	144,0	11,6	258,0	27+no of cores+cross section
12 x 1,5	172,8	12,3	310,0	27+no of cores+cross section
12 x 1,5 0Z	172,8	12,3	310,0	27+no of cores+cross section
14 x 1,5	202,0	12,8	360,0	27+no of cores+cross section
16 x 1,5	230,4	13,7	390,0	27+no of cores+cross section
18 x 1,5	259,2	14,7	420,0	27+no of cores+cross section
21 x 1,5	302,0	16,0	533,0	27+no of cores+cross section
25 x 1,5	360,0	17,2	600,0	27+no of cores+cross section
34 x 1,5	489,6	19,7	730,0	27+no of cores+cross section
40 x 1,5	576,0	21,5	895,0	27+no of cores+cross section
50 x 1,5	720,0	23,7	1060,0	27+no of cores+cross section

- Further formats available on request
- All data and products subject to change